

REPAIR MATERIAL FOR DAMAGED PAINT SURFACES

5 The invention relates to a repair material for repairing a layer of paint.

Minor paint damage is currently restored using repair kits which comprise, for example, a glass fibre stylus for the slight surface abrasion of the site to be repaired, and a
10 paint stylus (small reservoir for paint with an integrated brush). Alternatively, use is made of spray cans.

The use of paint styluses has the disadvantage that a smooth junction with the paint surrounding the site of the
15 repair is not obtained. Also, the repair area is often not reflectingly smooth. The utilisation of spray cans has the disadvantage that a veil of paint, which is likewise undesirable for aesthetic reasons, is often produced at the transitional region between the site of the repair and the
20 adjacent paint.

The intention is to indicate, by means of the present invention, a material with the aid of which minor paint damage can be repaired in a simple and high-quality manner.
25

This object is achieved, according to the invention, by means of a repair material which is designed after the fashion of a patch.

30 The repair patch is simply stuck on over the defective paint at the site to be restored and is then optionally heated up for hardening and/or for liquefying and subsequently solidifying the paint.

35 Since, in the repair material according to the invention, the paint material has not yet shrunk to form a brittle layer of paint, it can be successfully adapted even to convex surfaces.

Advantageous further developments of the invention are indicated in subclaims.

SUB A1
5 Layers of paint material, such as are indicated in claim 2, can be produced in a particularly simple manner by applying liquid synthetic-resin paint to a substrate and surface drying the paint.

SUB A2
10 If the surface dried layer of paint remains, until utilised in service, on a deformable substrate, as is indicated in claim 3, the repair material is distinguished by particularly satisfactory mechanical strength.

SUB A3
15 The further development of the invention according to claim 4 guarantees still greater deformability of the repair material, since a coherent layer of paint is not yet present in it at all. Nevertheless, the microcapsules guarantee homogeneous distribution of the paint material over the repair material, and such proximity of the
20 individual small volumes of paint that the paint material runs together, when released and optionally heated up, and forms a smooth reflecting surface.

SUB A4
25 What is achieved with the aid of the invention in accordance with claim 5 is that, after that bonding of the paint material with the layer of paint to be repaired which takes place under the action of heat, only the paint material is left on the repair area.

SUB A5
30 If particles of powder paint are put into the microcapsules in accordance with claim 6, in the first place the said particles form, after being melted down and cooled again, a layer of paint which is just as capable of being subjected to mechanical loads as the original paint. Furthermore,
35 the paint bonds particularly well with the material lying underneath it.

Sub
A6

A repair material such as is indicated in claim 7 needs no separate adhesive. It is also possible to simply lay the repair material on the repair area which has been heated up beforehand, where it is then fixed by the partial melting
5 of the microcapsules.

Sub
A7

The further development of the invention in accordance with claim 8 is of advantage with a view to the cost-effective manufacture of smaller pieces of repair material starting
10 from large sheets or preferably webs of the said repair material.

Sub
A8

What is achieved with the aid of the further development of the invention in accordance with claim 9 is that the user
15 has available, in a ready-prepared manner, pieces of repair material of different geometry and different size, that is to say, does not have to cut the repair material himself. Cutting of the repair material by the user might lead to irregularities at the edges.

Sub
A9

The further development of the invention in accordance with claim 10 permits adaptation of the colour of the repair material to paint which has become darker.

Sub
A10

25 In that connection, the advantage is achieved, with the aid of the further development of the invention in accordance with claim 11, that adaptation to the subsequent darkening can still be carried out by the user.

Sub
A11

30 This can be effected in a particularly simple manner in accordance with claim 12, through the fact that the user picks out, from a plurality of grey layers, the one which matches best.

35 The grey layers may, for example, be grids with a different grid-point size, which are printed in a black colour onto a transparent layer. For those paints which become lighter

as a result of atmospheric influences, use might also be made, in a similar manner, of "negative grey layers" manufactured by printing a grid pattern of reflective material onto a transparent layer. Alternatively, use
 5 might also be made of a white grid pattern for lightening purposes.

Sub
A12
 10 The further development of the invention in accordance with claim 13 makes it possible to keep a supply of only a single kit of repair material, with the aid of which it is then possible to cover a manufacturer's entire range of colours (optionally for a certain model only). This facilitates stock-keeping, particularly at the final vendor's premises.
 15

The invention will be explained in greater detail below with the aid of two exemplified embodiments and with reference to the drawings, in which:

20 figure 1: shows a section through a first repair material for layers of paint, in a direction perpendicular to the plane of the material;

figure 2: shows a view which is similar to that in
 25 figure 1 but in which a modified repair material is represented;

figure 3: shows a view which is similar to that in
 30 figure 1 and in which the repair material is additionally provided with a grey layer, in order to restore weathered paint; and

figure 4: shows a top view of pieces of repair
 35 material of different cut, which are contained in a kit in order to be able to carry out the restoration of painted regions of different shapes.

The repair material represented in figure 1 for a scratched or otherwise damaged layer of paint comprises a central base layer 10 which is manufactured from a flexible plastic material, for example a polypropylene film with a layer
 5 thickness of about 20 to 50 μm .

A layer of paint 12 is applied to the upper side of the base layer, for example by the spraying-on of a solvent-based paint and the subsequent drying-off of the said layer
 10 of paint. However, the paint is not hardened, with the result that it remains flexible and plastically deformable, in a manner similar to a prepreg.

The underside of the layer of paint 12 carries a layer of
 15 adhesive 14 with the aid of which the repair material can be attached to that painted area of a motor vehicle, sheet-metal casing or the like, which is to be repaired. Before the material is used, the layer of adhesive 14 is masked by a protective layer 16 which can be pulled off.

20 The modified repair material according to figure 2 consists of a layer 18 which, in turn, consists of microcapsules 20 and a bonding agent 22 which holds the latter together. Contained inside the microcapsules 20 is a paint material
 25 24 which, in this case, is shown as small droplets of paint but which may also be constituted by a small volume of powder-paint particles.

Islands of adhesive 26 are provided on the underside of the
 30 layer 18 in a regularly distributed manner.

The islands of adhesive 26, the bonding agent 22 and the walls of the microcapsules 20 are, in each case, manufactured from a material which evaporates and/or
 35 decomposes when acted upon by heat.

The way in which the repair material according to figure 2 is used, is that it is first applied to the area to be repaired and is smoothed down on the said repair area.

- 5 The islands of adhesive 26, the bonding agent 22 and the walls of the microcapsules 20 are then evaporated by supplying heat, and the contents of the various microcapsules 20 coalesce on the repair area to form a layer of paint. The said layer of paint can then be
10 hardened in the usual way by means of infrared radiation.

If a material which becomes sticky when heated up is chosen as the bonding agent 22 and/or as the material for the wall of the microcapsules 20, it is possible to dispense with
15 the islands of adhesive 26. In this case, the repair material is simply laid on the repair area which has been heated up beforehand, and is attached when partial melting of the bonding agent and/or of the microcapsules occurs. With a further increase in temperature, these materials are
20 then evaporated and the paint material comes into contact with the repair area. In the case of powder paint, further heating of the site of the repair leads to the melting-down of the powder-paint particles, which thus coalesce to form a coherent layer and are intimately bonded to the support.

25 The repair material shown in figure 3 is intended for restoring weathered paint. For this purpose, the repair material additionally comprises a grey layer 28 which accompanies a piece of repair material as a separate piece
30 of repair material. The repair kit comprises grey layers 28 having different grey values, so as to be able to restore paint which has been darkened to different degrees.

The grey layer 28 carries, on its underside, a transparent
35 layer of adhesive 30 which is masked by a protective layer 32 which is likewise transparent. In this way, the user can lay grey layers having different grey values over the

repair material on a trial basis, and decide which grey layer best reproduces the subsequent darkening which has occurred in the layer of paint.

- 5 After pulling off the protective layer 32, the user then sticks that grey layer 28 which produces the best match with the weathered paint, optically speaking, onto the upper side of the repair material, as is indicated in the left-hand part of figure 3. After its protective layer 16
10 has been pulled off, the repair material, which is thus adapted to the specific requirements, is stuck onto the painted region to be restored.

- In practice, different restoring operations can be carried
15 out on car paintwork or other paintwork. Thus, it may be necessary, on the paintwork of a car, to make good a long scratch produced with a sharp object, or else merely a small spot-shaped site which has been brought about by rust or the impact of a stone. It is accordingly possible, as
20 illustrated in figure 4, to make available a repair kit which comprises small, round pieces of repair material 34, rectangular pieces of repair material 36 and long, strip-shaped pieces of repair material 38, the latter being rolled up in the kit to form small coils.

- 25 In yet another further development of the invention, it is possible to market kits of pieces of repair material which not only comprise pieces of material of different geometry but also cover a manufacturer's entire standard range of
30 colours for a certain type of motor car. This simplifies stock-keeping.

- It will be recognised that it is possible, in the manner described above, to repair defective sites in layers of
35 paint in a simple way, without there being the risk of impairing the region surrounding the site of the repair. A

1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2